



**FEATURES**

- OS&Y
- WATER 2100 kpa @ 90°C
- FLANGES TO AS2129 TABLE F
- UNDRILLED
- PAINTED RED OXIDE PRIMER

∩ (CLOSED POSITION)

NO.	PART NAME	MATERIAL
1	BODY	DUCTILE IRON
2	BODY SEAT RING	BRONZE
3	WEDGE	DUCTILE IRON
4	WEDGE SEAT RING	BRONZE
5	STEM	SS420
6	BONNET BOLT	ZINCED CARBON STEEL
7	NUT	ZINCED CARBON STEEL
8	GASKET	GRAPHITE
9	BONNET	DUCTILE IRON
10	PACKING	GRAPHITE
11	BOLT	ZINCED CARBON STEEL
12	NUT	ZINCED CARBON STEEL
13	GLAND	DUCTILE IRON
14	BOLT	ZINCED CARBON STEEL
15	YOKE	DUCTILE IRON
16	STEM NUT	BRASS
17	MINIPAD	ZINCED CARBON STEEL
18	WHEEL	DUCTILE IRON
19	LOCKING NUT	BRASS

	TEST PRESSURE Mpa	
	SHELL	SEAT
API 598	3.2	2.1
HYDROSTATIC		
AIR		

SIZE	L	D	b	H
200	292	368	29	739
250	330	432	30.5	877
300	356	489	32	1011

REV	A	<b>BROOK VALVES</b> <b>B601FUD</b>
DATE	Mar-20	
SCALE	TO FIT	
RISING STEM WEDGED GATE VALVE FLANGED TABLE F UNDRILLED		