



FEATURES

- OS&Y
- WATER 2100 kpa @ 90°C
- FLANGES TO AS2129 TABLE F
- UNDRILLED
- PAINTED RED OXIDE PRIMER

↑ (CLOSED POSITION)

NO.	PART NAME	MATERIAL
1	BODY	DUCTILE IRON
2	BODY SEAT RING	BRONZE
3	WEDGE	DUCTILE IRON
4	WEDGE SEAT RING	BRONZE
5	STEM	SS420
6	BONNET BOLT	ZINCED CARBON STEEL
7	NUT	ZINCED CARBON STEEL
8	GASKET	GRAPHITE
9	BONNET	DUCTILE IRON
10	PACKING	GRAPHITE
11	GLAND	DUCTILE IRON
12	T BOLT	ZINCED CARBON STEEL
13	NUT	ZINCED CARBON STEEL
14	STEM NUT	BRASS
15	MINIPAD	ZINCED CARBON STEEL
16	WHEEL	DUCTILE IRON
17	LOCKING NUT	BRASS

TEST PRESSURE	Mpa	
	SHELL	SEAT
API 598	3.2	2.1
HYDROSTATIC		
AIR		

SIZE	L	D	b	H
50	178	165	20	289
65	190	184	20	340
80	203	203	22	387
100	229	229	24	450
150	267	305	26	594

REV	B	BROOK VALVES B601FUD
DATE	Nov-20	
SCALE	TO FIT	

↑ RISING STEM WEDGED GATE VALVE FLANGED TABLE F UNDRILLED